

Polypropylene Ductless Fume Hood-VAV



Topair's Polypropylene Ductless Fume Hoods provide a safe work environment for lab staff working with acids and harsh chemicals.

The hoods include an advanced VAV (Variable Air Volume) system with a VFD (Variable Frequency Driver). The VAV system measures the product's air velocity using a high quality sensor, and adjusts the air velocity speed to the relevant standard.

The system enables maximal energy savings, by flexibly adjusting the fan speed (high/low) to changing needs. The system features a high safety level, displaying real time air velocity and providing alarms for low velocity levels. This also reduces the fume Hood's noise level.

The products are **EN-14175 / CE / ASHRAE 110-1995 certified.**

NEW!

- Automatic airflow control (VAV system) with user friendly 4.3" color touch screen, settable operating speed, alarm speed, visual and audio alarms.
- Polypropylene structure, high chemical resistance
- Built-in sealed polypropylene worktop
- Optional stand
- Easily dissembled back wall
- Tempered glass sliding front window
- Top quality, quiet fan
- Eco-friendly, cost-effective 800 LUX LED lighting separated from the work area
- Wind speed at 0.5 m/s, 100 FPM
- Convenient front access for filter replacement
- Top filtration unit including variety of HEPA & carbon filters
- EN-14175 / CE / ASHRAE 110-1995 certified

Optional Features

PPS V2

ESD Protected




Active Charcoal Filter

LED Lighting

Control Panel & VAV System

Tempered Glass Window

Electric Outlets



Models

CUSTOM SIZES AVAILABLE!

Spec/ Model	CF-060-VAV	CF-090-VAV	CF-120-VAV	CF-150-VAV	CF-180-VAV
Outer Dimensions	600 x 750 x 1223 mm	900 x 750 x 1223 mm	1200 x 750 x 1223 mm	1500 x 750 x 1223 mm	1800 x 750 x 1223 mm
W x D x H	23.62 x 29.5 x 48"	35.4 x 29.5 x 48"	47.24 x 29.5 x 48"	59 x 29.5 x 48"	70.8 x 29.5 x 48"
Workspace (W x D x H)	585 x 610 x 695 mm 23 x 24 x 27.3"	885 x 610 x 695 mm 34.8 x 24 x 27.3"	1185 x 610 x 695 mm 46.6 x 24 x 27.3"	1485 x 610 x 695 mm 58.4 x 24 x 27.3"	1785 x 610 x 695 mm 70.2 x 24 x 27.3"
Front Sash Max. Opening	570 mm / 22.4"				
Production / Test Standard	EN-14175 / CE / ASHRAE 110-1995				
Air Velocity	0.5±0.1 m/s, 100±20 FPM				
Hood Material	Welded white polypropylene structure with built-in sealed polypropylene worktop				
Noise Level	<52dB	<52dB	<54dB	<60dB	<62dB
	(Tested 20 cm from the work table, 1.2m above ground)				
Power Supply	110 / 220V, 50/60 Hz, Single phase				
Illumination	800 LUX, Eco-friendly LED lighting				
Filter	Charcoal Filter/ multi-gas filter/HEPA				

Accessories

Description	Model
Metal stand	CF-size-ST
Polypropylene base cabinet	CF-size-BS
UV light	CF-UV
Gas tap	CF-GTAP
Water tap	CF-WTAP
Polypropylene cup sink	CF-PP-SINK
Polypropylene sink 30 x 40	CF-SINK-3040
Power outlet installed	CF-SOCKET

Tel : +1-855-6-TOPAIR (+1-855-686-7247) Email: sales@topairsystems.com

Web: www.topairsystems.com | Headquarters USA: 8912 68th Avenue Forest Hills New York 11375, USA